

Y6 Low VOC ABS Solvent Cement - 38Y6

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Y6 Low VOC ABS Solvent Cement - 38Y6
PRODUCT USE: Low VOC Cement for ABS Plastic Pipe
SUPPLIER: IPS Corporation
 777 McKay Road,
 Pickering, Ontario L1W 3A3
 Phone: 800 888-8312

EMERGENCY: Transportation: CANUTEC, 1 (613) 996-6666

Medical: CANUTEC, 1 (613) 996-6666

SECTION 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

		<u>Health</u>			
Acute (Oral) Toxicity:	Category 3	Skin Irritation:	Category 2	Specific Target Organ Toxicity (single exposure)	Category 3
Acute (Dermal) Toxicity:	Category 3	Serious Eye Damage	Category 2	Specific Target Organ Toxicity (repeated exposure)	Category 2
Acute (Inhalation) Toxicity:	Category 3				

GHS CLASSIFICATION: Classified according to Canada's Hazardous Products Regulations (WHMIS 2015).

		<u>Health</u>		<u>Environmental</u>	
Skin Irritation:	Category 2	Specific Target Organ Toxicity	Category 3	Acute Toxicity:	None Known
Serious Eye Damage	Category 2	Specific Target Organ Toxicity	Category 2	Chronic Toxicity:	None Known
				<u>Physical</u>	
				Flammable Liquid	Category 2

GHS LABEL:



Signal Word: DANGER

Hazard Statements

H225: Highly flammable liquid and vapor
 H302: Harmful if swallowed
 H315: Causes skin irritation
 H319: Causes serious eye irritation
 H332: Harmful if inhaled
 H335: May cause respiratory irritation
 H336: May cause drowsiness or dizziness
 H373: May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

P201: Obtain special instructions before use
 P202: Do not handle until all safety precautions have been read and understood
 P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
 P233 + P403: Keep container tightly closed. Store in a well-ventilated place
 P240 + P241: Ground/bond container and receiving equipment. Use explosion-proof equipment
 P242 + P243: Use only non-sparking tools. Take precautionary measures against static discharge
 P261: Avoid breathing dust/fume/gas/mist/vapors/spray
 P501: Dispose of contents/ container to an approved waste disposal plant

Response

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/Medical Attention
 P331: Do NOT induce vomiting.
 P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+313: IF exposed or concerned: Get medical advice/attention.

Percentage of Ingredients Unknown of Acute Dermal Toxicity:

0%

Physical Hazards Not Otherwise Classified

Vapours may form explosive mixture with air.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	CAS	EINECS	REACH		CONCENTRATION
			Registration Number		% by Weight
Methyl Ethyl Ketone (MEK)	78-93-3	201-159-0	01-2119457290-43-0000		50 - 60
Acetone	67-64-1	200-662-2	01-2119471330-49-0000		10 - 20
(ABS) Acrylonitrile/Butadiene/Styrene Copolymer #	9003-56-9	618-371-8	Not registered		20 - 30
Cyclohexanone	108-94-1	203-631-1	01-2119453616-35-0000		1 - 5

All of the constituents of this adhesive product are listed on the TSCA inventory of chemical substances maintained by the US EPA, or are exempt from that listing.

* Indicates this chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).

indicates that this chemical is found on Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 4 - FIRST AID MEASURES

Contact with eyes: Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately.
Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice.
Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.
Ingestion: Rinse mouth with water. Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do Not Induce Vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. Immediately call a Poison Centre or doctor.

SECTION 5 - FIREFIGHTING MEASURES

Suitable Extinguishing Media:	Foam, dry chemical, carbon dioxide or any Class B extinguishing agent	HMIS	NFPA	0-Minimal
Unsuitable Extinguishing Media:	Water spray or stream.	Health	2	2
Exposure Hazards:	Inhalation and dermal contact	Flammability	3	3
Combustion Products:	Oxides of carbon and smoke	Reactivity	0	0
		PPE	B	4-Severe

Unusual Fire and Explosion Hazards: Vapours may ignite explosively. Vapours may spread long distances. Prevent build-up of vapours. Extinguish all pilot lights and turn off heaters, non-explosion-proof electrical equipment and all other sources of ignition. Keep away from and do not store or use near heat, sparks or flames caused by such sources as electricity, static discharge, welding, grinding or flamecutting operation. Ground all equipment. Use spark-proof tools and conductive shoes to avoid sparking hazards.

Protection for Firefighters: Evacuate area. Fight fire from a safe distance or a protected location. For a massive fire, immediately evacuate the area and use unmanned hose holder or monitor nozzles. Before entry, especially into confined areas, use an appropriate monitor to check for: flammable or explosive atmosphere. Chemical protective clothing (e.g. chemical splash suit) and positive pressure SCBA may be necessary.

Y6 Low VOC ABS Solvent Cement - 38Y6

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep away from heat, sparks and open flame.
Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment.
Prevent contact with skin or eyes (see section 8).

Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course.

Methods for Cleaning up: Contain spill using noncombustible material such as vermiculite, earth or sand. Place used absorbent into suitable, covered, labelled containers for disposal. Contaminated absorbent poses the same hazard as the spilled product.

Materials not to be used for clean up: Aluminum or plastic containers. Do not use absorbents.

SECTION 7 - HANDLING AND STORAGE

Handling: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Electrically bond and ground equipment. Ground clips must contact bare metal. Use non-sparking tools. Wash hands thoroughly after handling this material. No smoking. Avoid breathing in this product. Do not get in eyes, on skin or on clothing. Do not swallow. Avoid exposure during pregnancy and while nursing.
Only use where there is adequate ventilation. Avoid generating vapours or mists.

Storage: Keep storage area separate from populated work areas. Store in a cool, dry, well ventilated area, out of direct sunlight and away from incompatible materials and any source of ignition. Ventilation fans and electrical equipment should be non-sparking.
Follow all precautionary information on container label, product bulletins and solvent cementing literature.

ATTENTION: Emptied containers may retain hazardous residue and explosive vapours. Keep away from heat, sparks and flames. Do not cut puncture or weld near this container. Follow label warning until container is thoroughly cleaned or destroyed.

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:	Component	ACGIH 8-hr TLV	ACGIH 15-min STEL	OSHA 8-hr PEL	Ontario OEL-TWA	Ontario STEL / Ceiling	CAL/OSHA 8-hr PEL	CAL/OSHA Ceiling	CAL/OSHA 15-min STEL
	Methyl Ethyl Ketone (MEK)	200 ppm	300 ppm	200 ppm	N/E	N/E	200 ppm	N/E	300 ppm
	Cyclohexanone	20 ppm	50 ppm	50 ppm	N/E	N/E	25 ppm	N/E	N/E
	Acetone	250 ppm	500 ppm	1000 ppm	N/E	N/E	500 ppm	3000 ppm	750 ppm

Engineering Controls: Use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Control static electricity discharges which includes bonding of equipment to ground. Provide safety shower in work area, if contact or splash hazard exists.

Monitoring: Maintain breathing zone airborne concentrations below exposure limits.

Personal Protective Equipment (PPE):

Eye Protection: Avoid contact with eyes, wear splash-proof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields, etc. as may be appropriate for the exposure.

Skin Protection: Prevent contact with the skin as much as possible. Butyl rubber gloves should be used for frequent immersion.
Use of solvent-resistant gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.

Respiratory Protection: Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above.
With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment. An organic vapour cartridge respiratory mask shall be worn to prevent the inhalation of vapours or spray mist when the TLB or PEL is exceeded. If respiratory protection is required, institute a complete respiratory protection program. Refer to the CSA Standard Z94.4 M1982 "Selection, Care and Use of Respirators" available from the Canadian Standard Association, Rexdale, Ontario. M9W 1R3

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Yellow	Physical State:	Liquid
Odour:	Ketone	Odor Threshold:	No information available
pH:	Not Applicable	Percent Volatile by Volume:	70%
Melting/Freezing Point:	-77 °C (-124 °F) (melting) (based on MEK)	Boiling Range:	57 °C (135 °F)
Initial Boiling Point/Range	57 °C (135 °F) (based on MEK)	Evaporation Rate:	3.7 (n-butyl acetate = 1) (based on MEK)
Flash Point:	-18 °C (-0.4 °F) (closed cup)	Flammability:	Category 2
Specific Gravity:	0.87 at 20 °C	Flammability Limits:	LEL: 1.4%
Solubility:	Soluble in water		UEL: 11.4%
Partition Coefficient n-octanol/water:	Not Available	Vapor Pressure:	105 mm Hg (24.7 kPa) @ 20 °C Acetone
Auto-ignition Temperature:	404 °C / 759.2 °F (based on MEK)	Vapor Density:	2.41 (Air = 1) (based on MEK)
Decomposition Temperature:	Not Applicable	Other Data: Viscosity:	Not Available
VOC Content:	When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: ≤ 325 g/l.		

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Normally stable.

Reactivity: Heating may cause a fire

Hazardous decomposition products: None in normal use. When forced to burn, this product gives off oxides of carbon and smoke.

Conditions to avoid: High temperatures. Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials: Oxidizing agents (e.g. peroxides).

Y6 Low VOC ABS Solvent Cement - 38Y6

SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Inhalation, Eye and Skin Contact

Acute symptoms and effects:

Inhalation: Excessive exposure to vapours or spray mists can result in headache, dizziness, incoordination and loss of consciousness. Irritation of the eyes, nose, throat and lungs can also occur when exposed to high vapour concentrations. Some reports have associated repeated and prolonged occupational overexposure to solvents with permanent nervous system damage.

Eye Contact: Vapors slightly uncomfortable. Overexposure may result in severe eye injury with corneal or conjunctival inflammation on contact with the liquid.

Skin Contact: Liquid contact may remove natural skin oils resulting in skin irritation. May cause defatting and irritation of skin (Dermatitis) upon prolonged or repeated contact.

Ingestion: Swallowing can cause nausea, vomiting, diarrhea and loss of consciousness.

Chronic (long-term) effects: (MEK): Low level chronic exposure has been shown to cause decreased memory and impairment of the central nervous system.

Health Hazards Not Otherwise Classified: This material may cause defatting and irritation of skin (Dermatitis) upon prolonged or repeated contact.

Respiratory or Skin Sensitization: Not Applicable

Toxicity:	LD50	LC50	Target Organs
Methyl Ethyl Ketone (MEK)	Oral: 2737 mg/kg (rat), Dermal: 6480 mg/kg (rabbit)	Inhalation 8 hrs. 23,500 mg/m ³ (rat)	STOT SE3
Cyclohexanone	Oral: 1535 mg/kg (rat), Dermal: 948 mg/kg (rabbit)	Inhalation 4 hrs. 8,000 PPM (rat)	Not Established
Acetone	Oral: 5800 mg/kg (rat), Dermal: 20000 mg/kg (rabbit)	Inhalation 50,100 mg/m ³ (rat)	STOT SE3
Acrylonitrile/Butadiene/Styrene (9003-56-9)	Oral: 5000 mg/kg (rat), Dermal: 2000 mg/kg (rabbit)	Not Established	Not Established

Acute Toxicity

Methyl Ethyl Ketone (MEK)	Acute (Oral) Toxicity: None	Acute (Dermal) Toxicity: None	Acute (Inhalation) Toxicity: None
---------------------------	-----------------------------	-------------------------------	-----------------------------------

Specific Target Exposure Toxicity (Single Exposure): Category 3

Specific Target Exposure Toxicity (Repeated Exposure): Not Applicable

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Established	Not Established	Not Established	Not Established	Not Established	Not Established

Carcinogenicity: (ABS) Acrylonitrile-Butadiene-Styrene Co-Polymer: On Proposition 65's List of chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity:	LC50	LC50	EC50
Acute Aquatic Toxicity	Pimephales promelas (fathead minnow); 96-hour	Daphnia magna (water flea); 48-hour	Pseudokirchneriella subcapitata (microalgae) Growth rate inhibitor
	Methyl Ethyl Ketone > 100 mg/L Acetone No Data Available Cyclohexanone 527 mg/L	> 100 mg/L 7630 > 100 mg/L	2,029 mg/l - 96 hour No Data Available 0.925 mg/l - 72 hour

Mobility in Soil: If released into the environment, this product can move rapidly through the soil.

Degradability: Does not degrade rapidly based on quantitative tests. (Tetrahydrofuran)

Bioaccumulation: This product and its degradation products are not known to bioaccumulate..

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Dispose of waste and containers in compliance with applicable Federal, State, Provincial, and Local regulations. Consult disposal expert.

SECTION 14 - TRANSPORT INFORMATION

Proper Shipping Name: Adhesives, Flammable (Acetone, Methyl Ethyl Ketone)	EXCEPTION for Ground Shipping
Hazard Class: 3	
Secondary Risk: None	DOT Limited Quantity: Up to 1L per inner packaging, 30 kg gross weight per package. Consumer Commodity: Depending on packaging, these quantities may qualify under DOT as ORM-D Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code: Not Applicable
Identification Number: UN 1133	
Packing Group: PG II	
Label Required: Class 3 Flammable Liquid	TDG INFORMATION
Marine Pollutant: NO	TDG CLASS: FLAMMABLE LIQUID 3
Special Precautions : Not Applicable	SHIPPING NAME: Adhesives, Flammable (Acetone, Methyl Ethyl Ketone)
	UN NUMBER/PACKING GROUP: UN 1133, PG II

SECTION 15 - REGULATORY INFORMATION

Precautionary Label Information: Highly Flammable, Irritant	Ingredient Listings: USA TSCA, Europe EINECS, Canada DSL, Australia
Symbols: F, Xi	AICS, Korea ECL/TCCL, Japan MITI (ENCS)
Risk Phrases: R11: Highly flammable. R20: Harmful by inhalation. R36/37: Irritating to eyes and respiratory system.	R66: Repeated exposure may cause skin dryness or cracking R67: Vapors may cause drowsiness and dizziness
Safety Phrases: S9: Keep container in a well-ventilated place. S16: Keep away from sources of ignition - No smoking. S25: Avoid contact with eyes.	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S33: Take precautionary measures against static discharges. S46: If swallowed, seek medical advise immediately and show this container or label.
Compliance Statement: This SDS was prepared to be in accordance with: US OSHA Hazard Communication Standard 29 CFR 1910.1200 (Rev 2012) Canadian Workplace Hazardous Materials Information System (WHMIS) 2015	Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL) All ingredients are listed on the DSL/NDSL.

SECTION 16 - OTHER INFORMATION

Specification Information:		
Department issuing data sheet:	IPS, Safety Health & Environmental Affairs	All ingredients are compliant with the requirements of the European Directive on RoHS (Restriction of Hazardous Substances).
E-mail address:	<EHSinfo@ipscorp.com>	
Training necessary:	Yes, training in practices and procedures contained in product literature.	
Reissue date / reason for reissue:	3/9/2021/ Updated GHS Standard Format	
Intended Use of Product:	Cement for ABS Plastic Pipe	

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.